



COMPONENTS

A

KERNMANTLE ROPE

B

LARGE KARABINER FOR LIFELINE CONNECTION

C

ROPE GRAB ADJUSTER

D

SHORT LANYARD FOR HARNESS CONNECTION.

PRODUCT CODES

SBWPL003K

3 Mtr. ADJUSTABLE WORK POSITIONING LANYARD

SBWPL005K

5 Mtr. ADJUSTABLE WORK POSITIONING LANYARD

SBWPL010K

10 Mtr. ADJUSTABLE WORK POSITIONING LANYARD

SBWPL020K

20 Mtr. ADJUSTABLE WORK POSITIONING LANYARD

DESCRIPTION

Work Positioning Lanyards and Work Restraint Lanyards are designed to hold the user in restraint, so a fall cannot occur.

An Adjustable Work Positioning Lanyard is used to protect a person working on an open edge when connected directly to an Anchor point or as part of a Work restraint system.

It allows the person using the lanyard to tension the lanyard easily by working the grab which operates on a one-way cam that prevents forward movement when adjusted and locked.

IDENTIFICATION & SUITABILITY



The information label carries the following information which should be visible.

Product code

Date of manufacture

Serial Number

Material

Size / length

Static strength

CE code logo and test facility reference

Compliance to EN353-2-2002

SafetyRespect Height safety components are individually serial numbered for traceability and supplied with a certificate of conformity.

Adjustable Work Positioning Lanyards don't have deceleration devices and should not be used in Fall Arrest applications.

Adjustable Work Positioning Lanyards are supplied with an Instruction Manual and Inspection Sheet, copies of which can be downloaded from www.safetyrespectstore.co.uk

We are here to help

If you are in any doubt about the condition of your Adjustable Work Positioning Lanyard please email us from our contact page.

www.safetyrespectstore.co.uk